

| HAULMASTER OPTIONS | 1100 | 1300N | 1300 | 1500 | 1700 | 2000 | 2300 |
|---|------|-------|------|----------------|------|------|------|
| IF 1250/50R32 CFO | S | S | S | | | -- | |
| 800/60R32 Steerable Inline Tandem (SteerLock available w/CONNECT only) ² | 0 | 0 | 0 | S | | -- | |
| LT378 Large Track (36" x 170") | 0 | 0 | 0 | 0 | S | S | S |
| VF 520/84R42 CFO Row Crop Tandem | 0 | 0 | 0 | | | -- | |
| 900/60R32 Steerable Inline Tandem (SteerLock available w/ CONNECT only) ² | | -- | | | 0 | | -- |
| 1050/50R32 Steerable Inline Tandem (SteerLock available w/ CONNECT only) ² | | -- | | | 0 | 0 | -- |
| TT324 Transfer Track (30" x 140") | 0 | | | -- | | | |
| TT324 Transfer Track (36" x 140") | 0 | 0 | 0 | | | -- | |
| Tandem Brakes (for 2 wheels only) ² | 0 | 0 | 0 | 0 | 0 | 0 | -- |
| Track Brakes ² | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 5-Point Scale | 0 | 0 | 0 | 0 | S | S | S |
| Haulmaster CONNECT | 0 | 0 | 0 | S ⁴ | 0 | 0 | 0 |
| Haulmaster PRO | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| External CONNECT Scale Display | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Agrimatics Scale Indicator | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Digistar GT560 Scale Indicator | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Manual Tarp | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Electric Tarp | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Hydraulic Jack ² | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Tow Hitch w/ Rope Hanger | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| CAT 4 Hitch | S | S | S | S | S | S | S |
| CAT 5 Articulating Hitch | -- | -- | -- | -- | 0 | 0 | 0 |
| 2 Ag Cam Kit (Back up and Spout) | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Mud Scrapers (Track) | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Fire Suppression System ² | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

| SPECIFICATIONS 1100-1300(N) w/TT324 & 1500-2300 w/ LT378 | 1100 | 1300N | 1300 | 1500 | 1700 | 2000 | 2300 |
|---|------------|---------------------|------------|------------|------------|------------|------------|
| Width | 12' 2" | 12' 2" ¹ | 13' 5" | 13' 5" | 14' | 14' | 14' |
| Overall Length | 32' 3" | 32' 3" | 32' 10" | 32' 10" | 38' | 38' | 38' |
| Tank Length | 22' 8" | 22' 8" | 23' 3" | 23' 3" | 28' 3" | 28' 3" | 28' 3" |
| Loading Side Height | 10' 2" | 11' | 10' 5" | 11' | 10' 6" | 11' 4" | 12' 2" |
| Transport Height | 11' 4" | 12' 2" | 11' 9" | 12' 4" | 12' | 12' 9" | 13' 6" |
| Auger Max Height | 14' 9" | 14' 9" | 16' | 16' | 16' 4" | 16' 4" | 16' 4" |
| Auger Max Reach | 9' | 9' | 10' | 10' | 9' 8" | 9' 8" | 9' 8" |
| Ground Clearance w/ Standard Undercarriage | 1' 6" | 1' 6" | 1' 6" | 1' 3" | 1' 3" | 1' 3" | 1' 3" |
| Empty Weight w/ Large Tracks | 30,500 lbs | 30,800 lbs | 31,100 lbs | 31,400 lbs | 33,300 lbs | 34,400 lbs | 35,600 lbs |
| Empty Weight w/ 36" Transfer Tracks | 28,600 lbs | 28,900 lbs | 29,200 lbs | | -- | | |
| Empty Weight w/ Tires & Wheels (1250 Tires) | 22,100 lbs | 22,400 lbs | 22,700 lbs | | -- | | |
| Empty Weight w/ Row Crop Tandem (520 Tires) | 24,900 lbs | 25,200 lbs | 25,500 lbs | | -- | | |
| Empty Weight w/ Steerable Inline Tandem | 26,400 lbs | 26,700 lbs | 27,000 lbs | 27,300 lbs | 32,500 lbs | 33,600 lbs | -- |
| Tongue Weight | 4,000 lbs | 4,000 lbs | 4,000 lbs | 4,100 lbs | 4,400 lbs | 4,400 lbs | 4,600 lbs |
| Unloading Auger | 22" | 22" | 22" | 22" | 24" | 24" | 24" |
| Horizontal Auger | 22" | 22" | 22" | 22" | 22" | 22" | 22" |
| Hydraulic Remotes ³ | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| Required Tractor HP (KW) | 225 (170) | 250 (190) | 250 (190) | 300 (225) | 350 (260) | 400 (300) | 450 (340) |

| UNDERCARRIAGE GROUND CONTACT AREA | 1250 SINGLE TIRE | 520 ROW CROP TANDEM | 800 INLINE TANDEM | 900 INLINE TANDEM | 1050 INLINE TANDEM | TT324 TRACK | LT378 TRACK |
|--------------------------------------|---------------------|---------------------------|-------------------------|-------------------------|--------------------------|----------------|----------------|
| Contact Area (in ²) | 3,050 | 2,950 | 3,950 | 4,800 | 5,600 | 6,400 | 9,200 |

¹ With Row Crop Tandem, Width is 12'
² Option Adds 1 Remote
³ Haulmaster Pro Reduce to 1 Remote
⁴ Standard with Inline Tandem

Legend: (0 - Optional) (S - Standard) (-- Not Available)

HAULMASTER

LEFT OR RIGHT HAND AUGER



#HAULMASTER
 f i t y l n
 ELMERSMFG.COM



HAULMASTER

AVAILABLE HAULMASTER MODELS:

1100, 1300N, 1300, 1500, 1700, 2000 & 2300

AVAILABLE COLOURS:



UNDERCARRIAGE OPTIONS

| MODEL | ROW CROP TANDEM | FLOTATION TIRES | INLINE TANDEM WITH STEERLOCK | TRANSFER TRACKS | LARGE TRACKS |
|-----------------|-----------------|-----------------|------------------------------|-----------------|--------------|
| 1100 - 1300 (N) | X | X | X | X | X |
| 1500 | | | X | | X |
| 1700 - 2000 | | | X | | X |
| 2300 | | | | | X |

INDUSTRY LEADING TECHNOLOGY

HAULMASTER CONNECT

SIMPLE INTERFACE TO INTERACT WITH YOUR HAULMASTER FEATURES.

- Detailed load tracking.
- No batteries required.
- Information stored on controller, not tablet.



STEERLOCK SYSTEM*

THE INDUSTRY-FIRST INTELLIGENT INLINE TANDEM LOCKING SYSTEM.

- Auto engage at high speeds.
- Auto engage when travelling in reverse.
- Increased stability and ease of use.

*Only available on Inline Tandem with Haulmaster Connect.

POWERMMASTER

Custom Designed Direct Drive Gearbox

CUSTOM DESIGNED DIRECT-DRIVE GEARBOX ELIMINATES BELTS WHILE INCREASING THROUGHPUT EFFICIENCY.

- Reduces maintenance.
- Improves grain flow efficiency.
- Exceptionally low profile design.

HAULMASTER PRO



EASY-TO-USE HYDRAULIC SYSTEMS GIVES THE OPERATOR ADVANCED TOOLS TO BE FASTER AND MORE EFFICIENT.

- Industry-exclusive double tap to fold/unfold auger.
- Industry-leading auger fold/unfold speed.
- Auto spout return home on fold.
- Comfortable joystick control for gate, pivot, fold and spout.

