

HAULMASTER



UNMATCHED CAPACITY & STABILITY

MASSIVE 2500 AND 3000 BU CAPACITY
ALL NEW TRACK DESIGN

Elmer's
MANUFACTURING

#HAULMASTER



ELMERSMFG.COM



AVAILABLE HAULMASTER MODELS:

1100, 1300N, 1300, 1500, 1700, 2000, 2300, 2500 & 3000

AVAILABLE COLOURS:



UP TO 16'+ AUGER SPOUT CLEARANCE
WITH 30 DEGREE AUGER PIVOT RANGE

CUSTOM TARP SYSTEM
(ELECTRIC OR MANUAL
OPTIONS AVAILABLE)

LARGE FRONT AND REAR WINDOWS
CLEAR VISIBILITY FOR SAFER TRANSPORT
AND EASY GRAIN LEVEL CHECKS

POWERMASTER DIRECT-DRIVE GEARBOX
ELIMINATES BELTS, CHAINS, AND SUMP

BOLT-TOGETHER DESIGN

CLEAN AND EFFICIENT WIRING WITH GROMMETS
AND HIGH QUALITY CONNECTORS

LARGE FULL-LENGTH CLEANOUT
FASTER CROP CHANGES AND PREVENTS GRAIN
CONTAMINATION

OPTIONAL
TOW HITCH



WHAT'S NEW

JOHN DEERE WEIGHT SHARING SYSTEM / HM CONNECT

Streamline harvest logistics with real-time grain cart weight data across the fleet. The system reads load cell sensors, transmits weight data to the scale display and improves communication between cabs.

PIPE AG / HM CONNECT COMPATIBILITY

This plug-and-play kit adds a Bluetooth connection between HaulMaster CONNECT and a PIPE AG tablet to display the weight of your grain cart.

TESTIMONIALS

"With the cart's low profile, you never have to worry about hitting your combine spout."

MYCHAL NEUMILLER (NEUMILLER HARVESTING)

"When a farmer looks at something, they know when it's well made. Elmer's grain carts are second to none."

TERRY PEGG (T&M PEGG FARMS)

"The HaulMaster's features are far superior to other carts I've been around. The right-hand auger delivery convinced us to buy - it just makes sense."

TODD ENEY (ENEY FARMS)



INDUSTRY-LEADING TECHNOLOGY

HAULMASTER PRO




EASY-TO-USE HYDRAULIC SYSTEMS GIVES THE OPERATOR ADVANCED TOOLS TO BE FASTER AND MORE EFFICIENT.

- Industry-exclusive double tap to fold/unfold auger.
- Industry-leading auger fold/unfold speed.
- Auto spout return home on fold.
- Auto gate close at 5 MPH, reducing liability of leaving the gate open.
- Auto gate close at predefined truck weight.

HAULMASTER CONNECT

SIMPLE INTERFACE TO INTERACT WITH YOUR HAULMASTER FEATURES.

- Detailed load tracking.
- No batteries required.
- Information stored redundantly on controller and tablet.
- Includes tablet, window mount and charger for a turnkey solution.



STEERLOCK SYSTEM*

THE INDUSTRY-FIRST INTELLIGENT INLINE TANDEM LOCKING SYSTEM

- Auto engage at high speeds.
- Auto engage when travelling in reverse.
- Increased stability and ease of use.

**Only available on Inline Tandem with HaulMaster CONNECT.*



CONNECT cloud.

MANAGE HARVEST DATA ANYWHERE

- Sync cart information with the cloud and have it accessible on a web browser, showing cumulative data from multiple carts.
- Users can back up farm information and save cart parameters online.

TERRAWAVE TRACKS

LARGER CONTACT AREA ENHANCES STABILITY AND CONTROL.

- Increased footprint: 42" x 128".
- Superior Traction: Innovative pivoting frame and double oscillating bogies ensure better stability and performance even in the roughest field.
- Maximum Uptime: Grease-free bushings and oil bath hubs mean less maintenance and more hauling.
- Higher weight capacity and standard mudscrapers.



HAULMASTER OPTIONS	1100	1300N	1300	1500	1700	2000	2300	2500	3000
IF 1250/50R32 CFO	S	S	S				--		
VF 520/85R42 CFO Row Crop Tandem	0	0	0				--		
800/60R32 Steerable Inline Tandem (SteerLock available w/CONNECT only) ²	0	0	0	S			--		
900/60R32 Steerable Inline Tandem (SteerLock available w/ CONNECT only) ²			--		S		--		
1050/50R32 Steerable Inline Tandem (SteerLock available w/ CONNECT only) ²			--		0	S		--	
TT324 Transfer Track (30" x 88")	0					--			
TT324 Transfer Track (36" x 88")	0	0	0				--		
LT378 Large Track (36" x 128")	0	0	0	0	0	0	S		--
TW36x128 Track (36" x 128")	0	0	0	0	0	0	0		--
TW42x128 Track (42" x 128")			--		0	0	0	S	S
Tandem Brakes (for 2 wheels only)	0	0	0	0	0	0		--	
Track Brakes	0	0	0	0	0	0	0	0	0
5-Point Scale	0	0	0	0	S	S	S	S	S
Haulmaster CONNECT	0	0	0	S ⁴	0	0	0	0	0
Haulmaster PRO	0	0	0	0	0	0	0	0	0
External CONNECT Scale Display	0	0	0	0	0	0	0	0	0
Agrimatics Scale Indicator	0	0	0	0	0	0	0	0	0
Digistar GT560 Scale Indicator	0	0	0	0	0	0	0	0	0
PIPE AG	0	0	0	0	0	0	0	0	0
John Deere Weight Sharing System	0	0	0	0	0	0	0	0	0
Manual Tarp	0	0	0	0	0	0	0	0	0
Electric Tarp	0	0	0	0	0	0	0	0	0
Hydraulic Jack ²	0	0	0	0	0	0	0	S	S
Tow Hitch w/ Rope Hanger	0	0	0	0	0	0	0	0	0
CAT 4 Hitch	S	S	S	S	S	S	S	S	S
CAT 5 Articulating Hitch	0	0	0	0	0	0	0	0	0
2 Ag Cam Kit (Back up and Spout)	0	0	0	0	0	0	0	0	0
Mud Scrapers (Track)	0	0	0	0	0	0	0	S	S
Fire Suppression System ²	0	0	0	0	0	0	0	0	0

SPECIFICATIONS	1100	1300N	1300	1500	1700	2000	2300	2500	3000
1100-1300(N) w/ TT324, 1500-2300 w/ LT378 & 2500-3000 w/ TW42									
Width	12' 2" ¹	12' 2" ¹	13' 4"	13' 4"	14'	14'	14'	14'	14'
Overall Length	32' 3"	32' 3"	32' 10"	32' 10"	38'	38'	38'	42' 11"	42' 11"
Tank Length	22' 8"	22' 8"	23' 3"	23' 3"	28' 3"	28' 3"	28' 3"	33' 8"	33' 8"
Loading Side Height	10' 1"	11'	10' 5"	11'	10' 6"	11' 4"	12' 2"	11' 5"	12' 3"
Transport Height	11' 3"	12' 1"	11' 10"	12' 4"	11' 10"	12' 9"	13' 6"	12' 10"	13' 9"
Auger Max Height	14' 9"	14' 9"	16'	16'	16' 4"	16' 4"	16' 4"	16' 7"	16' 7"
Auger Max Reach	9'	9'	10'	10'	9' 8"	9' 8"	9' 8"	9' 8"	9' 8"
Ground Clearance w/ Standard Undercarriage	1' 6"	1' 6"	1' 6"	1' 3"	1' 3"	1' 3"	1' 3"	1' 0.5"	1' 0.5"
Empty Weight w/ TerraWave Tracks			--					40,300 lbs	40,500 lbs
Empty Weight w/ Large Tracks	30,500 lbs	30,800 lbs	31,100 lbs	31,400 lbs	33,300 lbs	34,400 lbs	35,600 lbs	--	
Empty Weight w/ 36" Transfer Tracks	28,600 lbs	28,900 lbs	29,200 lbs			--			
Empty Weight w/ Tires & Wheels (1250 Tires)	22,100 lbs	22,400 lbs	22,700 lbs			--			
Empty Weight w/ Row Crop Tandem (520 Tires)	24,900 lbs	25,200 lbs	25,500 lbs			--			
Empty Weight w/ Steerable Inline Tandem	26,400 lbs	26,700 lbs	27,000 lbs	27,300 lbs	32,500 lbs	33,600 lbs		--	
Tongue Weight	4,000 lbs	4,000 lbs	4,000 lbs	4,100 lbs	4,400 lbs	4,400 lbs	4,600 lbs	5,200 lbs	5,200 lbs
Unloading Auger	22"	22"	22"	22"	24"	24"	24"	24"	24"
Horizontal Auger	22"	22"	22"	22"	22"	22"	22"	22"	22"
Hydraulic Remotes ³	4	4	4	4	4	4	4	5	5
Required Tractor HP (KW)	225 (170)	250 (190)	250 (190)	300 (225)	350 (260)	400 (300)	450 (340)	480 (360)	560 (420)

UNDERCARRIAGE	1250 SINGLE TIRE	520 ROW CROP TANDEM	800 INLINE TANDEM	900 INLINE TANDEM	1050 INLINE TANDEM	TT324 TRACK	TW36 TRACK	TW42 TRACK
GROUND CONTACT AREA								
Contact Area (in ²)	3,050	2,950	3,950	4,800	5,600	6,400	9,200	10,720

Legend: (0 - Optional) (S - Standard) (-- Not Available)

¹ With Row Crop Tandem, width is 12'. ² Option adds 1 remote. ³ HaulMaster PRO reduce to 1 remote on 1100-2300, 2 remotes on 2500-3000. ⁴ Standard with Inline Tandem