CROPCOMMANDER

HIGH-CAPACITY
GRAIN CONVEYOR



Elmer's MANUFACTURING

FEATURES

- Handles all grain and seed types.
- Hydraulic tensioning system provides constant tension, regardless of changes in belt length.
- Dual stack pump and bypass system reduces hydraulic power draw, making more power available to move crop.
- Ride-on operator platform for ease of mobility around yard.
- Towable at 32 km/hr (20mph).
- Fuel Tank Capacity 24 gal.
- Belt scrapers for continuous cleaning; One at intake, two at discharge.





Elmer's Grain Conveyor is still in development and subject to features and specification changes.

SPECIFICATIONS

Performance	
Capacity (bushels per hour)	up to 14,000 Bu/Hr
Horsepower - Gas	40 hp
Dimensions	
Belt Width	24"
Belt Take-up	80"
Conveyor Length	50'
Raised Height	22' 2"
Raised Reach	22' 5"
Lowered Height	12' 6"
Lowered Reach	25' 6"
Maintenance Height	5' 10"
Transport Height	13' 10"
Transport Length	55' 5"
Intake Reach	12'
Wheel Track Width	8' 5"
Total Weight	6800 lb
Tube Diameter	13"
Tire Size	225/75R15
Hopper	
Hopper Width and Length	30" x 60"
Hopper Collapsed Height	12"
Hopper Raised Height	24"
Maximum Speed	
Fast-Low Torque	8 km/hr
Slow-High Torque	4 km/hr

Elmer's MANUFACTURING

Phone: 1 204 324 6263
Box 908, Altona, MB, CA, R0G 0B0
Box 357, Neche, ND, USA, 58265
Website: elmersmfg.com

Version_1.2_08_20_2026